

# CR 15-X

Highly versatile and compact computed radiography solution offering high image quality and high speed

- Affordable for a broad range of applications
- Convenient and fast workflow, with usercontrollable speed and resolution
- Robust yet easy to install and maintain
- Fits in small spaces and is suited for mobile applications
- Networking capabilities deliver seamless integration
- Highly versatile, compact CR 15-X offers and ideal solution for decentralised hospital environments, clinics and private practices.

The tabletop CR 15-X digitizer is based on proven Agfa HealthCare technology, with a modular yet robust design combining affordability with high image quality, adjustable speed and a user-tuned workflow.

Versatile, this computed radiography (CR) digitizer can handle a broad range of digital radiography applications.

The total cost of ownership remains low, thanks to its ease of installation, maintenance and use, making it an affordable way to move from analog to digital. With the CR 15-X, decentralised hospital environments, clinics and private practices can take advantage of the convenient and fast workflow offered by digital radiography.

## Balancing speed and resolution

With the CR 15-X, the user can choose to adjust speed and resolution depending on the needs of the exam. The user can easily overwrite the default settings for each exam, depending on the specific speed/quality priorities, study by study. Agfa HealthCare's intelligent MUSICA image processing automatically optimizes image quality.



# CR 15-X DIGITIZER



## Robust yet easy to install and maintain

Installing the CR 15-X is fast and easy. With its 'one screwdriver' concept and modular, component-based design, maintenance is faster, easier and more cost-effective, as well. Consequently, set up costs are lower and installation simpler. Horizontal cassette insertion prevents dust and dirt from being introduced during normal operation.

## Fits in small spaces and is suited for mobile applications

With its table-top size, the CR 15-X digitizer can be placed easily at any location, no matter how small, and was designed with ease of use in mind. The CR 15-X can also be fitted into cars, vans, trucks and other mobile facilities, for mobile applications. Due to the low power consumption, connection to battery can be easily realized.

## Networking capabilities deliver seamless integration

The CR 15-X is fully DICOM-compliant, to easily integrate with other solution elements; we recommend combining it with Agfa HealthCare's SE software suite for a complete softcopy solution, or with the DRYSTAR 5302 imager for a hardcopy solution.

### CASSETTE SIZES

	Cassette Sizes	Spatial Resolution
■ CR MD1.0 GENERAL	35 x 43 (14 x 17")	10 pixels/mm (including for Full Leg/Full Spine) 6.6 pixels/mm 5 pixels/mm (including for Full Leg/Full Spine)
■ CR MD1.0 GENERAL	24 x 30	10 pixels/mm 6.6 pixels/mm 5 pixels/mm
■ CR MD1.0 GENERAL	18 x 24	10 pixels/mm 6.6 pixels/mm 5 pixels/mm
■ CR MD1.0 GENERAL	15 x 30	10 pixels/mm 6.6 pixels/mm 5 pixels/mm

## Technical Specifications

### GENERAL

#### Digitizer type

- Single cassette feed
- Throughput: Up to 102 plates/hour (depending on size and resolution)

#### Display

- LED Status Indicator
- Status and error messages on external PC monitor

#### Greyscale resolution

- Data acquisition: 20 bits/pixel
- Output to processor: 16 bits/pixel square root compressed

#### Dimensions and weight

- (W x D x H): 580 x 700 x 471 mm  
Depth without cassette unit and extension: 380 mm
- Weight: 30 kg

#### Power

- Autoranging external power supply (24V output)
- Input:
  - 100V - 240V
  - < 2A
  - 50/60 Hz
  - fuse: Europe max 16A; USA max 15A

#### Minimum requirements

- CR MD1.0 GENERAL PLATE
- CR MD1.0 GENERAL CASSETTE
- CR MD1.0 CASSETTE ADAPTER 24 X 30
- NX

#### Environmental conditions

- In line with: IEC 721-3-3 (1997): class 3K2, with the following extension:
  - Temperature: 15 - 35° C

#### Environmental effects

- Noise level: max. 65 dB (A)
- Heat dissipation: standby 30 W, max. 140 W

#### Mobile use

- In line with IEC721-3-3 (1997): 3K2 with the following restrictions:
  - Temperature: +15° C to +35° C
  - Humidity: 15 - 75 % RH (non-condensing)
  - During transport with mobile kit: in line with IEC721-3-5: 5K1 and 5M3

#### Transport

- In line with: IEC 721-3-2 (1997): class 2K2, with the following restrictions: -25 to +55° C (-4 to 131° F)

#### Storage

- Packed device shall withstand the following mechanical conditions: IEC 721-3-1: class 1M2 and IEC 721-3-2 (1993): class 2M3; including sea transport.
- In line with IEC721-3-1: class 1K4

### SAFETY

#### Approvals

- CE, cNRTLus

#### SAFETY

##### General

The product has been designed in accordance with the MEDDEV Guidelines relating to the application of Medical Devices and has been tested as a part of the conformity assessment procedures required by 93/42/EEC Medical Device Directive (European Council Directive) 93/42/EEC on Medical Devices).

- ISO 13485:2003
- IEC 62366:2007
- IEC 62304:2006
- ISO 14971:2007

##### Safety

- IEC 60601-1:2005
- UL 60601-1:2003
- CAN/CSA C22.2 No 601.1-M90

##### Laser Safety

- IEC 60825-1:1993
- IEC 60825-1:2007

##### Electromagnetic Compatibility

- IEC 60601-1-2:2007
- FCC Rules 47 CRF part 15 subpart B
- CAN/CSA 22.2 No 60601-1-2-08

##### Environmental Compliance

- WEEE 2012/19/EC
- RoHS 2 Directive 2011/65/EU

## CR 15-X DIGITIZER

### Insight. Delivered.

Agfa HealthCare is a global leader in the fast growing market of integrated IT and imaging systems, offering healthcare facilities a seamless flow of information and a 360° view of patient care. The company has a unique, holistic approach, enabling it to provide in-depth clinical know-how and fully integrated hospital-wide solutions. These specialized solutions integrate IT and imaging systems for Radiology, Cardiology, Mammography, Orthopaedics and Veterinary Care. Agfa HealthCare's enterprise-wide IT platform integrates all administrative and clinical data within a healthcare facility and is designed to match the unique needs of specific healthcare professionals. ■

[www.agfahealthcare.com](http://www.agfahealthcare.com)

Agfa and the Agfa rhombus are trademarks of Agfa-Gevaert N.V., Belgium, or its affiliates. All other trademarks are held by their respective owners and are used in an editorial fashion with no intention of infringement. The data in this publication are for illustration purposes only and do not necessarily represent standards or specifications, which must be met by Agfa HealthCare. All information contained herein is intended for guidance purposes only, and characteristics of the products and services described in this publication can be changed at any time without notice. Products and services may not be available for your local area. Please contact your local sales representative at [agfa.com](http://agfa.com) for availability information. Agfa HealthCare diligently strives to provide as accurate information as possible, but shall not be responsible for any typographical error.

© 2013 Agfa HealthCare NV  
All rights reserved  
Published by Agfa HealthCare NV  
B-2640 Mortsel - Belgium  
5ZLFO GB 00201311